


STD. DOUBLE-QUICK-MOUNT BENDING GENERATORS PRE-MOUNTED AND WIRED, TWO ENDS



DESCRIPTION

When a mechanical force causes a suitably wired and polarized 2-layer element to bend, one layer is compressed and the other is stretched. Charge develops across each layer in an effort to counteract the imposed strain. This charge may be collected for strain sensing or power generation.

Double Quick-Mount bending sensors save users the trouble of mounting and wiring transducer elements. They are easily attached and removed from equipment using the two clearance holes in the PCB mount. They are wired for parallel operation. The user may opt to remove the board mounted bleed resistor which protects the transducer and user electronics from transient voltages arising from thermal and mechanical shocks. The user mounts the transducer to the source of mechanical strain.

Standard Double Quick-Mount Benders employ T220-A4-103X, T220-A4-203X, T220-A4-303X or T220-A4-503X standard brass reinforced transducers.

Standard Double Quick-Mount Benders are more economically priced than other Double Quick-Mount configurations, and are generally stocked for immediate delivery.

Dimensions for Standard Double-Quick-Mounts are shown on [page 46](#).

Custom configurations and sizes: Upon request.

ROHS: Compliant.

PERFORMANCE: DOUBLE QUICK-MOUNT BENDING GENERATORS (Cantilever mount)

VALUES TO BE USED AS GUIDELINES

PART NUMBERS DOUBLE QUICK-MOUNT BENDING GENERATORS	PIEZO MATERIAL	WEIGHT (grams)	STIFFNESS (N/m)	CAPACITANCE (nF) (Parallel Operation)	RATED TIP DEFLECTION ① (mm _{peak})	RATED FREQUENCY ① (Hz)	OPEN CIRCUIT VOLTAGE ① At rated deflection, parallel operation (V _{peak})	CLOSED CIRCUIT CURRENT ① Per sinusoidal cycle, at rated deflection, parallel operation. (μA _{peak} / Hz)	RATED OUTPUT POWER ① At rated deflection and frequency (mW _{rms})
D220-A4-103YB	5A4E	1.1	6.1×10 ¹	12	± 1.0	100	± 14.9	± 2.0	.37
D220-A4-203YB	5A4E	1.7	1.2×10 ²	23	± 1.0	120	± 14.9	± 3.9	.88
D220-A4-303YB	5A4E	2.7	3.6×10 ²	46	± .84	145	± 14.9	± 7.9	2.1
D220-A4-503YB	5A4E	10.4	1.9×10 ²	232	± 2.6	47	± 20.9	± 52	6.4

-103, -203, and -303 Double Quick-Mount bending generator performance is based on an active extension length of 1.0". -503 performance based on 2.0" active length. Double Quick-Mount performance is based on the force being applied at the outermost tip of the mount.

PRICE & ORDERING INFORMATION

PART NO.

1 pc

5

25

100

Std Double QM Bending Generator, -103 Size	D220-A4-103YB	\$184	\$104	\$69	\$53
Std Double QM Bending Generator, -203 Size	D220-A4-203YB	\$189	\$114	\$74	\$56
Std Double QM Bending Generator, -303 Size	D220-A4-303YB	\$209	\$134	\$84	\$67
Std Double QM Bending Generator, -503 Size	D220-A4-503YB	\$249	\$179	\$134	\$109